

APR 07 2010**PATENT**
PATENT APP. SER. NO. 10/046,404
ECLIPSE GROUP DOCKET NO. H103027USU (P02017US)**AMENDMENTS****TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): An acoustic waveguide, comprising:
 - a first control curve;
 - a second control curve;
 - a third control curve;
 - a fourth control curve; and
 - a continuous three-dimensional surface coincident with the first control curve, the second control curve, the third control curve and the fourth control curve that ~~intersect~~intersects a circular throat end and a non-elliptical closed control ~~surface~~curve that defines a mouth.
2. (canceled).
3. (original): The acoustic waveguide of claim 1, wherein the continuous three-dimensional surface further includes: a minimum surface area axial section plane of the continuous three-dimensional surface formed from the first control curve, second control curve, third control curve, and fourth control curve.
4. (original): The acoustic waveguide of claim 3, wherein the minimum surface area axial section plane is at the circular throat end of the acoustic waveguide.
5. (currently amended): The acoustic waveguide of claim 1, wherein the first control curve is symmetrical about ~~[[an]]~~a first axis with the second control curve.
6. (currently amended): The acoustic waveguide of claim 5, wherein the third control curve is symmetrical about ~~[[the]]~~a second axis with the fourth control curve.
7. (previously presented): A method for creation of an acoustic waveguide, comprising:
 - identifying a first control curve;
 - identifying a second control curve that mirrors the first control curve;

PATENT
PATENT APP. SER. NO. 10/046,404
ECLIPSE GROUP DOCKET NO. H103027USU (P02017US)

- identifying a third control curve;
identifying a fourth control curve that mirrors the third control curve; and
generating a continuous three-dimensional surface formed by extending the first control curve, second control curve, third control curve and fourth control curve to intersect a circular throat end and a non-elliptical closed control curve forming a mouth.
- 8-10. (canceled).
11. (currently amended): The acoustic waveguide of claim 3, where the minimum surface area axial section plane is disposed at a midsection of the acoustic waveguide axially between the circular throat end and the non-elliptical closed control surfacecurve.
12. (currently amended): An acoustic waveguide, comprising:
a first control curve;
a second control curve;
a third control curve;
a fourth control curve; and
a continuous three-dimensional surface swept about a central axis of the acoustic waveguide with minimal discontinuities and coincident with the first control curve, the second control curve, the third control curve and the fourth control curve that ~~intersect~~intersects a circular throat end and a non-elliptical closed control surfacecurve that defines a mouth.
13. (currently amended): An acoustic waveguide, comprising:
a first control curve;
a second control curve;
a third control curve;
a fourth control curve; and
a continuous three-dimensional surface coincident with the first control curve, the second control curve, the third control curve and the fourth control curve that ~~intersect~~intersects a circular throat end and a non-elliptical closed control surfacecurve that defines a mouth, the continuous three-dimensional surface comprising a minimum surface area axial section plane formed from the first control curve, second control curve, third control curve, and fourth control curve, where the minimum surface area axial

PATENT
PATENT APP. SER. NO. 10/046,404
ECLIPSE GROUP DOCKET NO. H103027USU (P02017US)

section plane is disposed at a midsection of the acoustic waveguide axially between the circular throat end and the non-elliptical closed control ~~surface~~curve.

14. (currently amended): An acoustic waveguide, comprising:
 - a first control curve;
 - a second control curve;
 - a third control curve;
 - a fourth control curve; and
 - a continuous three-dimensional surface coincident with the first control curve, the second control curve, the third control curve and the fourth control curve that ~~interseet~~intersects a circular throat end and a non-elliptical closed control ~~surface~~curve that defines a mouth, where each of the first, second, third and fourth control curves is convergent-divergent relative to an axial centerline of the acoustic waveguide.
15. (previously presented): The acoustic waveguide of claim 12, wherein the continuous three-dimensional surface further includes a minimum surface area axial section plane of the continuous three-dimensional surface formed from the first control curve, second control curve, third control curve, and fourth control curve.
16. (previously presented): The acoustic waveguide of claim 15, wherein the minimum surface area axial section plane is at the circular throat end of the acoustic waveguide.
17. (currently amended): The acoustic waveguide of claim 15, where the minimum surface area axial section plane is disposed at a midsection of the acoustic waveguide axially between the circular throat end and the non-elliptical closed control ~~surface~~curve.
18. (currently amended): The acoustic waveguide of claim 12, wherein the first control curve is symmetrical about ~~[[an]]~~a first axis with the second control curve.
19. (currently amended): The acoustic waveguide of claim 12, wherein the third control curve is symmetrical about ~~[[the]]~~a second axis with the fourth control curve.
20. (canceled).
21. (currently amended): The acoustic waveguide of claim 13, wherein the first control curve is symmetrical about ~~[[an]]~~a first axis with the second control curve.

PATENT
PATENT APP. SER. NO. 10/046,404
ECLIPSE GROUP DOCKET NO. H103027USU (P02017US)

22. (currently amended): The acoustic waveguide of claim 13, wherein the third control curve is symmetrical about ~~[[the]]~~ a second axis with the fourth control curve.
23. (canceled).
24. (previously presented): The acoustic waveguide of claim 14, wherein the continuous three-dimensional surface further includes a minimum surface area axial section plane of the continuous three-dimensional surface formed from the first control curve, second control curve, third control curve, and fourth control curve.
25. (currently amended): The acoustic waveguide of claim ~~[[23]]~~ 24, wherein the minimum surface area axial section plane is at the circular throat end of the acoustic waveguide.
26. (currently amended): The acoustic waveguide of claim ~~[[23]]~~ 24, where the minimum surface area axial section plane is disposed at a midsection of the acoustic waveguide axially between the circular throat end and the non-elliptical closed control ~~surface~~ curve.
27. (currently amended): The acoustic waveguide of claim 14, wherein the first control curve is symmetrical about ~~[[an]]~~ a first axis with the second control curve.
28. (currently amended): The acoustic waveguide of claim 14, wherein the third control curve is symmetrical about ~~[[the]]~~ a second axis with the fourth control curve.